

Safety Data Sheet (SDS)

United Colors of the DVX — Car Wash V5 Red

DVX1067 DVX1055 DVX1074

Product name on SDS	UNITED COLORS OF THE DVX - RED
Regulation	REACH Annex II — Regulation (EU) 2020/878 · CLP (EC) 1272/2008
Revision / date	Rev. 3 · 28.01.2026
Number of pages	16
Supplier	Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Emergency	+90 216 669 03 53
UFI	G313-20MW-2001-MKMG

This cover page identifies the product. The following pages are the official Safety Data Sheet prepared in accordance with applicable regulations and are presented unchanged.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code:

Product name **UNITED COLORS OF THE DVX - RED**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **not available**

1.3. Details of the supplier of the safety data sheet

Name **SETKIM KIMYA INS.TAAH.PAZ.SAN.TIC.LTD.STI.**

Full address **İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20**

District and Country **34935 Tuzla / İstanbul (Türkiye)**

TR

Tel. tel. +90 216 669 03 53

Fax Fax +90 216 669 03 50

e-mail address of the competent person responsible for the Safety Data Sheet **info@divortex.com.tr**

1.4. Emergency telephone number

For urgent inquiries refer to **tel. +90 216 669 03 53**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.
Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Skin corrosion, category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:	Danger
Hazard statements:	
H314	Causes severe skin burns and eye damage.
Precautionary statements:	
P260	Do not breathe dust / fume / gas / mist / vapours / spray.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P310	Immediately call a POISON CENTER / doctor
P264	Wash with water thoroughly after handling.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
Contains:	SODIUM HYDROXIDE 1-HYDROXYETHYLIDENE -1,1-DIPHOSPHONIC ACID ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
WATER		
INDEX -_80 x < 90		
EC 231-791-2		
CAS 7732-18-5		
SODIUM HYDROXIDE		
INDEX 011-002-00-6_4 x < 5	Skin Corr. 1A H314, Eye Dam. 1 H318	
EC 215-185-5__Skin Corr. 1B H314: 2%, Skin Irrit. 2 H315: 0.5%, Eye Dam. 1 H318: 2%, Eye Irrit. 2 H319: 0.5%		
CAS 1310-73-2		
1-HYDROXYETHYLIDENE -1,1-DIPHOSPHONIC ACID		
INDEX -_4 x < 5	Met. Corr. 1 H290, Acute Tox. 4 H302, Eye Dam. 1 H318	
EC 220-552-8		STA Oral: 500 mg/kg
CAS 2809-21-4		
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS		
INDEX -_2 x < 3	Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 3 H412	
EC 500-234-8		
CAS 68891-38-3		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.
SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.
INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.
INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT
The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.
UNSUITABLE EXTINGUISHING EQUIPMENT
None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE
Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

ESP	España	Límites de exposición profesional para agentes químicos en España 2021
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	TLV-ACGIH	ACGIH 2022

SODIUM HYDROXIDE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	

VLA	ESP		2	
NGV/KGV	SWE	1	2	INHAL
WEL	GBR		2	
TLV-ACGIH			2 (C)	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.
When choosing personal protective equipment, ask your chemical substance supplier for advice.
Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION
Protect hands with category III work gloves.
The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.
The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION
Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION
Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION
If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.
Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.
If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS
The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	**Value**	**Information**
Appearance	Liquid	
Colour	Red	

Odour	Characteristic
Melting point / freezing point	not available
Initial boiling point	not available
Flammability	Not flammable
Lower explosive limit	not available
Upper explosive limit	not available
Flash point	not available
Auto-ignition temperature	not available
Decomposition temperature	not available
pH	13-14
Kinematic viscosity	not available
Solubility	Soluble in water
Partition coefficient: n-octanol/water	not available
Vapour pressure	not available
Density and/or relative density	1-1,1 gr/ ml
Relative vapour density	not available
Particle characteristics	not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

1-HYDROXYETHYLIDENE -1,1-DIPHOSPHONIC ACID

Decomposes at temperatures above 200°C/392°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

SODIUM HYDROXIDE

Avoid exposure to: air,moisture,sources of heat.

10.5. Incompatible materials

SODIUM HYDROXIDE

Incompatible with: strong acids,ammonia,zinc,lead,aluminium,water,flammable liquids.

1-HYDROXYETHYLIDENE -1,1-DIPHOSPHONIC ACID

Incompatible with: strong oxidants,strong bases.

10.6. Hazardous decomposition products

1-HYDROXYETHYLIDENE -1,1-DIPHOSPHONIC ACID

May develop: phosphine,phosphoric acid,phosphoryl oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	Not classified (no significant component)

SODIUM HYDROXIDE

LD50 (Dermal):	1350 mg/kg Rat
LD50 (Oral):	1350 mg/kg Rat

1-HYDROXYETHYLIDENE -1,1-DIPHOSPHONIC ACID

STA (Oral):	500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS

LD50 (Dermal):	> 2000 mg/kg Rat
LD50 (Oral):	2870 mg/kg Rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS	
LC50 - for Fish	7.1 mg/l/96h Danio rerio
EC50 - for Crustacea	7.4 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	27.7 mg/l/72h Desmodesmus subspicatus
Chronic NOEC for Fish	0.14 mg/l Oncorhynchus mykiss
Chronic NOEC for Crustacea	0.27 mg/l Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	0.95 mg/l Desmodesmus subspicatus

12.2. Persistence and degradability

SODIUM HYDROXIDE	
Solubility in water	> 10000 mg/l
Degradability: information not available	
1-HYDROXYETHYLIDENE -1,1-DIPHOSPHONIC ACID	
Solubility in water	> 10000 mg/l
NOT rapidly degradable	
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS	
Solubility in water	2800 mg/l
Rapidly degradable	

12.3. Bioaccumulative potential

1-HYDROXYETHYLIDENE -1,1-DIPHOSPHONIC ACID	
Partition coefficient: n-octanol/water	-3.5
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS	
Partition coefficient: n-octanol/water	0.3

12.4. Mobility in soil

1-HYDROXYETHYLIDENE -1,1-DIPHOSPHONIC ACID	
Partition coefficient: soil/water	4.22
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS	
Partition coefficient: soil/water	0.34

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
Waste transportation may be subject to ADR restrictions.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1760

14.2. UN proper shipping name

ADR / RID: CORROSIVE LIQUID, N.O.S. (SODIUM HYDROXIDE; 1-HYDROXYETHYLIDENE -1,1-DIPHOSPHONIC ACID)
IMDG: CORROSIVE LIQUID, N.O.S. (SODIUM HYDROXIDE; 1-HYDROXYETHYLIDENE -1,1-DIPHOSPHONIC ACID)
IATA: CORROSIVE LIQUID, N.O.S. (SODIUM HYDROXIDE; 1-HYDROXYETHYLIDENE -1,1-DIPHOSPHONIC ACID)

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8
IMDG: Class: 8 Label: 8
IATA: Class: 8 Label: 8



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID:	NO
IMDG:	NO
IATA:	NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 80	Limited Quantities: 5 L	Tunnel restriction code: (E)
	Special provision: -		
IMDG:	EMS: F-A, S-B	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 856
	Passengers:	Maximum quantity: 5 L	Packaging instructions: 852
	Special provision:	A3, A803	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Met. Corr. 1	Substance or mixture corrosive to metals, category 1
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level

- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:
The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.
This document must not be regarded as a guarantee on any specific product property.
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety

laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.
Prepared by: Suna ÖNSAL
Document Number: KDU/11.284.07
Contact Information: info@divortex.com.tr
Document Validity Date: 10.07.2030

CALCULATION METHODS FOR CLASSIFICATION
Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.
Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.
Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:
The following sections were modified:
01.