

Contact Cleaning Spray (With Oil)

Cleaning spray with protective oil film for electrical contacts

AER1410 **AER1405**

PRODUCT DESCRIPTION

Used to clean electrical and electronic parts from dust, oil and other dirt. Thanks to its moisture-repelling action, it provides resistance against external influences such as rust and corrosion. Can be used at home, on garden tools, locks, headlight holders, plugs, hinges and curtain rails, as well as for oil cleaning. Helps solve problems in electrical and electronic circuits. Re-lubrication may be required after cleaning the surface. Periodic applications can prolong parts life.

FEATURES

- Deep contact cleaning
- Moisture & corrosion shield
- Protective oil film
- Smoother electrical contact
- Ozone-friendly propellant
- Extends equipment life

DIRECTIONS FOR USE

1. **Power off completely** — Disconnect all electrical power before use.
2. **Shake well** — Shake the can thoroughly before use.
3. **Spray from 15-20 cm** — Apply evenly to the contacts or connection.
4. **Let dry & operate** — Allow to dry, then move the mechanism several times.

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Aerosol contact cleaner
Appearance	Aerosol
Odour	Characteristic
Density (20 °C)	0.62-0.68 g/ml
Solubility in water	Insoluble in water
Flammability	Extremely flammable aerosol (see Section 2)
Flash point	-97 °C
Use	Ready to use (apply undiluted)

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER1410	200 ml	24 per case	8682960810879
AER1405	400 ml	24 per case	8682960810961

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).
Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Istanbul Leather OIZ, Fikse St. No:20, 34935 Tuzla / Istanbul, Türkiye · +90 850 259 0389 · info@divortex.com.tr