

Liquid Grease Spray (Lithium)

High-performance lithium grease for heavy dynamic loads

PRODUCT DESCRIPTION

A high quality grease lubricant that is both cold and heat resistant, built for heavy dynamic loads. Can also be used on machines while running. Good friction properties, suitable for motorcycle chains. Chains, sprockets, door hinges, rails, ball bearings, O-rings and X-rings, wire ropes and all kinds of dynamic joints benefit from long-lasting internal and external lubrication. Operates between -40°C and +200°C. Non-drip, high adhesion, corrosion-preventing, moisture- and water-repellent.

FEATURES

- Extreme-pressure power
- Friction & wear defense
- Long-lasting adhesion
- Water & corrosion resistance
- 360° spray
- Clear formula

DIRECTIONS FOR USE

1. **Shake well** — Shake the can thoroughly before use.
2. **Spray from 15-20 cm** — Apply an even coat to the surface to be lubricated.
3. **Let it set** — Allow the grease film to set before putting back into service.
4. **Repeat if needed** — For heavy loads or high-stress points, reapply as needed.

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Aerosol / automotive additive
Appearance	Aerosol
Colour	Colorless
Odour	Characteristic
pH	6-7
Density (20 °C)	0,70-0,80 gr/cm³
Solubility in water	Not soluble in water
Flammability	Flammable
Flash point	65°C

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H304 May be fatal if swallowed and enters airways.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
P211 Do not spray on an open flame or other ignition source.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).