

Mold Protection Spray

Protective spray for molds, against corrosion and rust

AER2416

PRODUCT DESCRIPTION

It forms an optimal and long-lasting resistant protective layer. It ensures strong saturation, pick-up quality, and fast drying. It has a double effect on metal, wood, glass, and ceramic surfaces. It protects against corrosion and rust, with effective protection on metals of mold pipelines, machines, etc. It creates a non-aqueous, water-resistant dry protection layer.

FEATURES

- Long-lasting protective film
- Fast-drying formula
- Corrosion & rust defense
- Water-resistant dry coat
- Aerosol can
- Full-cover cap

DIRECTIONS FOR USE

1. **Shake well** — Shake the can thoroughly before use.
2. **Clean the surface** — Remove dirt, oil and residue with a suitable cleaner.
3. **Spray from 20-30 cm** — Apply a thin, even coat across the surface.
4. **Allow to dry** — Wait until the protective film is completely dry.

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Aerosol / automotive additive
Appearance	Aerosol
Odour	Characteristics
Density (20 °C)	0,68-0,72 g/ml
Solubility in water	Insoluble in water
Use	Ready to use (apply undiluted)

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER2416	500 ml	24	—

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H350 May cause cancer.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects. Restricted to professional users.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
P211 Do not spray on an open flame or other ignition source.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).

Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Istanbul Leather OIZ, Fikse St. No:20, 34935 Tuzla / Istanbul, Türkiye · +90 850 259 0389 · info@divortex.com.tr