

Motorcycle Chain Cleaner Spray

Fast-acting motorcycle chain degreaser spray, safe on O/X/Z-ring chains

AER1700

PRODUCT DESCRIPTION

Fast acting, non-permanent, industrial oil and grease solvent spray. It is suitable for all metals and alloys. Compatible with all O-ring, X-ring and Z-ring chains. Dissolves all dirt, oil and other tarred industrial residues, leaving no residue. Used for cleaning oil, grease and tarred dirt on roller bearings, sliding bearings, hinges, motorcycle and industrial chains.

FEATURES

- Powerful deep clean
- Maximum chain performance
- Fast, residue-free
- O/X/Z-ring safe
- Aerosol can
- Full-cover cap

DIRECTIONS FOR USE

1. **Prepare & shake well** — Use before lubrication. Shake the can thoroughly.
2. **Spray from 15-20 cm** — Apply evenly to the chain and dirty surfaces.
3. **Wait 1-2 minutes** — Let it work, then brush or wipe away dirt.
4. **Lubricate the chain** — After cleaning, apply a suitable chain lubricant.

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Aerosol / automotive additive
Appearance	Aerosol
Odour	Characteristic
Density (20 °C)	0,60-0,70 g/ml
Solubility in water	Insoluble in water
Use	Ready to use (apply undiluted)

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER1700	500 ml	24	—

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H350 May cause cancer.
H340 May cause genetic defects.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects. Restricted to professional users.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
P211 Do not spray on an open flame or other ignition source.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).

Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Istanbul Leather OIZ, Fikse St. No:20, 34935 Tuzla / Istanbul, Türkiye · +90 850 259 0389 · info@divortex.com.tr