

Tyre & Bumper Renovator

Water-resistant tyre & bumper renovator with long-lasting UV protection

AER9123

PRODUCT DESCRIPTION

Tyre & Bumper Renovator is a water-resistant product with a special formulation that can be used for polishing, protection and revitalization on all types of tires and bumpers, providing long-term effect. Product which provides protection against dirt and UV rays, prevents the recurrence of dirt due to its high hydrophobicity. It has effective and long-lasting time even in adverse weather conditions.

FEATURES

- Restores tyres & plastic bumpers
- Water-resistant UV protection
- Long-lasting shine & protection
- Hydrophobic dirt-repellent finish
- 750 ml aerosol can
- Precision spray nozzle

DIRECTIONS FOR USE

1. **Clean, dry & shake** — Make sure the surface is clean and dry. Shake well.
2. **Spray from 20 cm** — Apply an even layer from approximately 20 cm away.
3. **Spread evenly** — Wait a few seconds, then spread with a dry microfiber cloth.
4. **Wait 10 minutes** — Keep the vehicle stationary for 10 minutes after application.

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Aerosol / automotive additive
Appearance	Aerosol
Colour	Transparent
Odour	Characteristic
Density (20 °C)	0,6-0,8 gr/ml
Flash point	48 - 50 °C
Use	Ready to use (apply undiluted)

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER9123	750 ml	12	—

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
P211 Do not spray on an open flame or other ignition source.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).

Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Istanbul Leather OIZ, Fikse St. No:20, 34935 Tuzla / Istanbul, Türkiye · +90 850 259 0389 · info@divortex.com.tr